99888-0195-01

Table of Contents

Specifications 1-2

Specifications

PERFORMANCE		
Minimum Turning Radius		2.6 m (8.5 ft)
DIMENSIONS		
Overall Length		1 980 mm (77.95 in.)
Overall Width		730 mm (28.7 in.)
Overall Height		1 035 mm (40.75 in.)
Wheelbase		1 370 mm (53.94 in.)
Road Clearance		170 mm (6.69 in.)
Curb Mass		135 kg (298 lb)
TRANSMISSION		
Driving System		Chain drive
Primary Reduction Ratio		3.211 (61/19)
Final Reduction Ratio		3.867 (58/15)
Overall Drive Ratio		12.414
FRAME		
Caster		24.4°
Trail		93 mm (3.7 in.)
Tire Size:	Front	100/80-17 M/C 52S
	Rear	130/70-17 M/C 62S
Rim Size:	Front	17M/C × MT2.75
	Rear	17M/C × MT3.50
Brake Fluid:	Front	DOT3 or 4
	Rear	DOT4
ELECTRICAL EQUIPMENT		
Motor Drive Battery Pack:	Type	50.4 V 30 Ah (× 2), Lithium-ion battery
	Weight	11.5 kg (25.4 lb) (× 2)
Battery		12 V 2.5 Ah (10 HR)
Headlight:	High Beam	LED
	Low Beam	LED
City Light		LED
Brake/Tail Light		LED
Turn Signal Light:	Front	LED
	Rear	LED
License Plate Light		LED

Even if any one element of LED (Light Emitting Diode) light does not go on, consult with an authorized Kawasaki dealer.

Specifications are subject to change without notice.